

Toroidal OPT : VDV-2512-SEE
Application : EL34 / KT88 / KT120 Single Ended
Power : 12 Watt
UL-tap : 33 % (GRN)
-3dB range Pent. : 33 Hz to 65 kHz (guitar)
-3dB range UL : 22 Hz to 75 kHz (hifi)
-3dB range Triode : 17 Hz to 70 kHz (high end)
Z-primair : 2,5 kOhm (RED=B+; YEL=Anode)
Z-secondair : 0/4/8 Ohm (BLK/BLU/GRY)
Io quiescent : 100 mA
Lp : 12 H
Lsp : 5,8 mH
Cip : 945 pF
Rip : 113 Ohm
Ris (0 to 4/8-Tap) : 0,29 / 0,53 Ohm
Dimensions : round 90 mm dia, 40 mm height

Supply transformer : 4N1885; 2 x 12 W Stereo SE
Application : mains power for EL34 / KT88 / KT120 Single Ended
Primary : 2 x 115 V 50/60 Hz
Sec-1 : 250 / 275 V @ 300 mA
Sec-2 : 6,3 V @ 2,5 A
Sec-3 : 6,3 V @ 2,5 A
Sec-4 : 50 V @ 100 mA
Dimensions : round 93 mm dia; height 50 mm

Availability

Amplimo b.v.

Industrieweg 14
7161 BX Neede The Netherlands
info@amplimo.nl
www.ringkertrafo.nl
tel: 0031-(0)545-283-456
fax: 0031-(0)545-283-456

(Europe: toroidal Vanderveen OPT's, toroidal power transformers, Amplimo/Vanderveen-kits, valves, special valve components, Vanderveen E-choke + MEC + Autobias)